

## LK205-U LK205-U/SIL



PEWA  
Messtechnik GmbH  
Weidenweg 21  
58239 Schwerte  
Tel.: 02304-96109-0  
Fax: 02304-96109-88  
E-Mail: info@pewa.de  
Homepage: www.pewa.de

Hoch flexible Messleitungen mit PVC- oder Silicon-Isolierung, beidseitig mit axialem, starrem Ø 2 mm-Stecker.

Highly flexible test leads with insulation in PVC or Silicone with in-line Ø 2 mm rigid plugs on both ends.

Cordons de mesure extra-souples à isolation en PVC ou Silicone, équipés des deux côtés d'une fiche rigide Ø 2 mm droite.

Typ Type Type	Best.-Nr. Order No. N° de Cde	Bemessungsspannung / -strom Rated voltage / current Tension / intensité assignée	Leitungsquerschnitt Lead cross section Section du câble		Längen [cm] Lead lengths [cm] Longueurs [cm]	*Farben *Colours *Couleurs
LK205-U	28.0050-□*	30 V <sub>AC</sub> ~ 60 V <sub>DC</sub> / 10 A	0,5 mm <sup>2</sup>	Au PVC	015 030 045 060	21 22
LK205-U/SIL	28.0051-□*	30 V <sub>AC</sub> ~ 60 V <sub>DC</sub> / 10 A	0,5 mm <sup>2</sup>	Au SIL	015 030 045 060	21 22