

Model IR610

Infrared Thermometer



The IR610 is a portable, easy-to-use 3½-digit, compact-sized digital infrared thermometer capable of measuring °C and °F temperature.

Pressing the laser button turns the sighting laser marker on and off.

Depress the large center button to turn on the meter for measuring temperature. Release the button to stop measuring temperature and automatically hold the display reading, the meter turns off automatically after 15 seconds.

IR610 Specifications (at 23°C±5°C, <75% R.H. non-condensing)

| Temperature | |
|-------------------------|--|
| Range | - 20 °C to 260 °C; 0 °F to 500 °F |
| Display Resolution | 1 °C; 1 °F |
| Accuracy | ± 3% of reading or ± 3 °C / ± 6 °F, whichever is greater @ 18 to 28°C ambient |
| Temperature Coefficient | ± 0.2 % of reading or ± 0.2 °C, whichever is greater, per °C, > 28°C or < 18°C |
| Response Time | 1 second |
| Spectral Response | 6 to 14mm nominal |
| Emissivity | Pre-set 0.95 |
| Detection Element | Thermopile |
| Optical Lens | Fresnal Lens |
| Field of View | 100 mm Ø at 1000 mm |
| Sighting | 1 - Laser beam marker < 1 mW (670 nm) Class |



General Specifications

Display: 3½-digit (LCD) with maximum reading of 1999; **Overrange:** (OL) or (-OL) is displayed; **Low Battery Indication:** Change batteries immediately; **Measurement Rate:** 2.5 times per second, nominal; **Operating Environment:** 0 °C to 50 °C (32 °F to 122 °F) at < 75% R.H.; **Storage Temperature:** - 20 °C to 60 °C (- 4 °F to 140 °F), 0 to 80 % R.H. with batteries removed; **Environment:** Indoor use, altitude up to 2000 m; **Battery:** 4 pieces 1.5 V (AAA size) UM-4, R03; **Battery Life:** 100 hours carbon-zinc battery; **Auto Power Off:** approximately 15 seconds; **Standby Current:** < 1 µA; **Dimensions:** 170 x 44 x 40 mm; **Weight:** 160 g including batteries; **Warranty:** One-year

- Laser pointer for accurate targeting
- Measures to 500 °F (260 °C), front panel switchable
- Narrow 10:1 field of view measures 1" at 10" distance
- Fixed emissivity at 0.95
- Certified to meet CE EN60825 Class II for laser safety
- Data hold, low battery indicator, auto power off
- Large, 3-1/2 digit display with backlight feature
- Shipped with carrying case, four AAA batteries installed and operator's guide



Model IR610

Infrared Thermometer

Meterman.
The right tool for the job.[™]



PEWA
Messtechnik GmbH

Weidenweg 21
58239 Schwerte

Telefon: +49 (0) 2304-96109-0
Telefax: +49 (0) 2304-96109-88
eMail: info@pewa.de
Homepage: www.pewa.de